SPRINKLERS

K ROTARY





FEATURES AND BENEFITS

- Durable design molded with high-impact engineered resin for long life
- Superior uniformity multi-stream technology provides outstanding coverage, eliminating brown spots.
- Matched precipitation low precipitation rate is proportionate even after arc and radius adjustment.
- Water smart technology reduces water use by up to 30% without sacrificing turf quality.
- Double pop-up design delivers additional protection from dirt/ particulate intrusion and harsh conditions.
- · Simple to adjust
- Color-coded 6 standard nozzles and 3 specialty nozzles in the field

Nozzle code	Pattern	Nozzle color	P (bar)	Width x Length (m)	Q (m³/h)
			2.06	1.22 x 4.6	1.14
Right end strip RNS-RES-515	0	Copper	2.46	1.5 x 4.6	1.21
			2.75	1.5 x 4.6	1.32
			3.10	1.8 x 4.9	1.43
			3.45	1.8 x 4.9	1.51
Left end strip RNS-LES-515		Olive	2.06	1.22 x 4.6	1.14
			2.46	1.5 x 4.6	1.21
			2.75	1.5 x 4.6	1.32
			3.10	1.8 x 4.6	1.43
			3.45	1.8 x 4.9	1.51
Side strip RN-SS-530	0	Brown	2.06	1.22 × 8.8	1.80
			2.46	1.5 x 9.1	2.08
			2.75	1.5 x 9.1	2.30
			3.10	1.8 x 9.4	2.46
			3.45	2.1 x 9.7	2.64



Telefon: 0431-222 90

Org.nr: 556409-6120

Bg.nr: 5743-7980





Pop-up I/2" adjustable K Rotary nozzles, designed to fit into a standard pop-up spray head, provide increased uniform coverage over conventional fixed pattern spray nozzles, while delivering matched precipitation.

The highly efficient water delivery reduces soil erosion and runoff, saving water and money.

A perfect solution for low water pressure areas while still delivering precise, even coverage.

RN - 100, 200, 300 Performance Table

RN 100 90-270 90° Green 2.41	Nozzle code	Pattern	Nozzle	P (bar)	D (m)	Q (m³/h)
RN 100 90-270 RN 100 360° RN 100 360° RN 200 90-270 RN 300		2		2.07	3.96	0.83
90-270 PO-270 PO-270			_			0.91
RN 100 90-270 RN 100 90-270 RN 100 90-270 RN 100 90-270 270° Green RN 100 360° RN 100 360° RN 200 90-270 RN 300 90-27		90°	Green			0.94
RN 100 90-270 PN 100 90-270 RN 100 360° RN 100 360° RN 200 90-270 RN 300						1.10
RN 100 90-270 RN 100 90-270 Po-270 Po-270		0 180°	Green		:	1.66
RN 100 90-270 90° Green 2.76 4.27 1.8 3.10 4.57 2.1 2.07 3.96 2.5 2.41 4.27 2.6 4.27 2.8 3.10 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.45 4.57 3.2 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1						1.78
RN 100 90-270 90° Green						1.89
RN 100 90-270						2.19
RN 100 90-270 Second Part						2.27
RN 100 90-270 270° Green 2.76 3.10 4.57 3.2 3.45 4.57 3.4 2.07 3.96 3.3 3.45 4.57 3.2 2.76 4.27 3.5 3.10 4.57 3.2 2.76 4.27 3.5 3.10 4.57 4.5 3.10 4.57 4.5 3.10 4.57 4.5 3.10 4.57 4.5 3.10 5.79 1.7 2.07 4.87 1.2 2.41 5.18 2.8 3.10 5.79 1.7 3.45 5.79 3.45 5.79 3.45 5.79 3.10 3.10 5.79 3.10 3.10 5.79 3.15 3.10 5.79 5.3 3.10 5.79 5.3 3.10 3.10 5.79 5.3 3.10 3.10 5.79 5.3 3.10 3.10 5.79 5.3 3.10 3.10 5.79 5.3 3.10 3.10 5.79 5.3 3.10 3.10 3.10 5.79 5.3 3.10 3.10 3.10 3.10 3.10 3.10 3.10 3.		270°				2.50
RN 200 90-270 RN 200 90-270 Blue Second			Green			2.84
RN 200 90-270 RN 200 90-270 PO° Blue Silve Silv						3.25
RN 100 360° 360° Blue 2.07						3.40
RN 200 90-270 PO° Blue 2.76		360°				3.33
RN 200 90-270 80	RN 100				:	3.56
RN 200 90-270 Blue Second						3.78
RN 200 90-270 Blue 2.07	300		OI CCII			4.35
RN 200 90-270 PN 200 90-270 RN 200 90-270 RN 200 90-270 Blue 2.41 2.76 3.10 3.79 3.15 3.10 3.79 3.10 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.10 5.79 3.1 3.45 5.79 5.3 3.41 5.88 5.60 5.48 6.2 3.10 5.79 6.3 3.10 8.83 3.5 6.3 3.45 8.53 3.5 6.3 3.45 8.53 3.5 6.3 3.45 8.53 3.5 6.3 3.45 8.53 3.5 6.3 8.5 8.53 3.7 8.7 8.7 8.7 8.7 8.7 8.7 8.7 8.7 8.7 8						4.54 1.29
RN 200 90-270 180° Blue 2.76 5.48 1.5 3.10 5.79 1.5 1.5 3.15 5.79 1.7 3.45 5.79 1.7 3.45 5.79 3.1 3.45 5.79 3.1 3.45 5.79 3.5 3.45 5.79 3.5 3.45 5.79 3.5 3.45 5.79 3.5 3.10 5.79 3.7 3.45 5.79 5.3 3.10 5.79 4.7 3.8 4.2 3.10 5.79 4.7 3.45 5.79 5.3 3.10 5.79 5.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 5.3 3.45 5.79 7.1 3.10 3.45 5.79 7.1 3.10 3.45 5.79 3.10 3.45 5.79 3.10 3.45 5.79 3.10 3.45 3.10 3.53 3.5 3.45 3.10 3.10 3.53 3.5 3.45 3.10 3.10 3.53 3.5 3.45 3.10 3.10 3.53 3.5 3.10	DA 1 200					1.44
RN 200 90-270 Blue		90°	Blue			1.55
RN 200 90-270 Blue 2.07	90-270		1			1.59
RN 200 90-270 Blue				3.45		1.78
RN 200 90-270 180° Blue 2.76 5.48 3.1		- I				2.53
RN 200 90-270 RN 200 360° Blue 270° Blue 2.76 3.10 3.45 5.79 3.5 2.27 4.87 3.8 2.41 5.18 4.2 2.76 5.48 4.6 3.10 5.79 4.87 5.0 3.10 5.79 4.87 5.0 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 6.3 3.10 8.54 6.2 2.76 8.23 3.45 8.53 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.7 8.85 3.10 8.85 3.66 8.23 6.0 8.83 8.83 8.83 8.85 8.83 8.85 8.83 8.85 8.83 8.85 8.83 8.85 8.83 8.85 8.83 8.85 8.85		0 180°	Dlue			2.84
RN 200 90-270 Blue 270° Blue 2.76			Diue			
RN 200 90-270 Blue 2.07 2.41 5.18 4.2 2.76 5.48 4.6 3.10 5.79 4.7 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 5.3 3.45 5.79 6.3 3.10 5.79 4.7 3.45 5.0 2.41 5.18 5.6 6.48 6.2 2.76 5.48 6.2 2.76 5.48 6.2 2.77 7.92 3.0 2.41 7.92 3.2 2.41 7.92 3.2 2.41 7.92 3.3 3.10 8.53 3.45 8.53 3.7 3.10 8.53 3.55 3.45 8.53 3.7 7.92 5.3 3.10 8.84 6.4 3.45 9.14 6.8 8.23 6.0 8.20 7.92 9.20 7.92 9.20 8.23 8.23 8.34 8.33 8.35 8.35 3.45 8.33 8.35 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.45 8.33 8.35 8.35 8.35 8.35 8.35 8.35 8.3						3.56
RN 200 90-270 RN 200 360° Blue 2.76		270°	Blue			3.82
90-270 RN 200 360° Light Blue 2.76 3.10 5.79 4.7 3.45 5.79 2.07 4.87 5.0 2.41 5.18 5.6 2.76 5.48 6.2 3.10 5.79 3.10 5.79 6.3 3.10 5.79 6.3 3.10 5.79 3.10 5.79 3.10 5.79 3.10 5.79 3.10 5.79 3.10 5.79 5.3 5.6 7.79 3.10 8.53 3.45 3.15 8.53 3.45 3.15 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 3.10 8.53 3.45 2.07 7.92 5.3 8.41 8.23 8.45 9.14 8.83 9.60 90.270 Grey 7.92 9.2 90.270 Grey 7.92 9.2 90.270 6.3 90.270 8.83 9.60 90.270 8.83 9.60 90.270 90.270 8.83				2.41	5.18	4.28
RN 200 360° Light Blue Second Process of Street Process of Stre						4.69
RN 200 360° Light Blue 2.07 4.87 5.0 2.41 5.18 5.6 2.76 5.79 6.3 3.45 5.79 7.1 2.07 7.92 3.0 2.41 7.92 3.2 2.41 7.92 3.2 2.76 8.23 3.4 3.10 8.53 3.5 3.45 8.23 3.4 3.10 8.53 3.5 3.45 8.23 3.4 3.10 8.53 3.5 3.45 8.23 3.4 3.10 8.53 3.5 3.45 8.23 3.4 3.10 8.53 3.5 3.45 8.23 6.0 90-270 Grey 2.76 8.23 6.0 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90-270 Grey 2.76 8.53 10.4						4.77
RN 300 90-270					:	
RN 300 90-270 180° Grey Grey Grey 180° Grey 2.76 3.10 5.79 6.3 3.45 5.79 7.1 2.07 7.92 3.0 2.41 7.92 3.2 2.41 7.92 3.3 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.53 3.45 8.63 3.10 8.84 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 RN 300 90-270 Grey 2.76 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 2.41 8.23 6.0 8.3 10.4 8.83 10.4 8.83 10.4		o 360°				
RN 300 90-270 90° Grey 2.76 8.23 3.45 8.53 3.7 RN 300 90-270 Grey 2.76 8.23 3.45 8.53 3.7 2.07 7.92 5.3 3.45 8.53 3.7 2.07 7.92 5.3 3.45 8.53 3.7 2.07 7.92 5.3 RN 300 90-270 Grey 2.76 8.24 8.23 5.6 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90-270 Grey 2.76 8.53 10.4						6.24
RN 300 90-270 90° Grey Grey Grey 2.07						6.36
RN 300 90-270 90° Grey 2.41 7.92 3.2 2.76 8.23 3.4 3.10 8.53 3.5 2.07 7.92 5.3 2.41 8.23 5.6 6.4 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90-270 Grey Grey Grey Grey Grey 2.41 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 8N 300 90.270 Grey Grey Grey 2.41 8.23 6.0 3.10 8.84 6.4 3.45 9.14 8.83 9.6 9.276 8.53				3.45	5.79	7.11
RN 300 90-270 90° Grey 2.76 8.23 3.4 3.10 8.53 3.5 3.7 2.07 7.92 5.3 RN 300 90-270 180° Grey 2.76 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90.270 270° Grey 2.76 8.33 10.4		90°	Grey		7.92	3.03
RN 300 90-270					:	3.22
RN 300 90-270						
RN 300 90-270 Grey 2.07 7.92 5.3 2.41 8.23 5.6 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90.270 Grey 2.76 8.53 10.4						3.78
RN 300 90-270 Grey 2.41 8.23 5.6 2.76 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90.270 Grey 2.76 8.53 9.66 2.70 8.83 9.66 3.10 8.84 6.4		180°	Grey			5.30
90-270 Grey 2.76 8.23 6.0 3.10 8.84 6.4 3.45 9.14 6.8 2.07 7.92 9.2 2.41 8.23 9.6 2.07 7.92 9.2 2.41 8.23 9.6 3.45 9.14 8.23 10.4						5.68
3.45 9.14 6.8 2.07 7.92 9.2 RN 300 90.270 Grey 2.76 8.53 10.4						6.05
RN 300 90.270 Grey 2.76 8.53 10.4						6.43
RN 300 270° Grey 2.41 8.23 9.6		270°			•	6.81
90-270 Grey 2.76 8.53 10.4			Grey			9.27
						10.41
				3.10	8.53	10.98
						11.73
2.07 7.92 11.7	RN 300 360	• 360°		2.07	7.92	11.73
RN 300 Light 2.41 8.23 12.1			Light Grey		8.23	12.11
360 Croy 2.76 8.53 13.2						13.25
3.10 8.53 13.4			0.07			13.43

Postadress:

TRÄDGÅRDSTEKNIK AB Helsingborgsvägen 578, Varalöv 262 96 ÄNGELHOLM **URL:**

www.tradgardsteknik.se E-postadress:

info@tradgardsteknik.se