

TECHNICAL DATA SHEET

GP77 TR/S

STRUCTURE



Gear Box/alternator monoblock unit coupled through shaft, installed on a welded, powder-painted carbon steel base frame with demountable legs. (images are for illustrative purpose only)

ELECTRIC PANEL

Magnetothermic circuit breaker
Earth fault device
125A 400V Socket
32A 230V Socket
Schuko sockets 16A 230V
E31 digital module:
- Voltmeter
- Frequency meter
- Hour counter

TECHNICAL DATA

EQUIPMENT SPECIFICATION (ISO 8528/1)	50Hz
Prime power at cosφ 0.8	75 kVA
Prime power at cosφ 0.8	60 kW
Voltage available to the terminals	400/230 V
Dimensions (mm)	1140x750x1065
Weight (Kg)	454

GEAR BOX	50Hz
Brand and model	6005.407.035
R.P.M.	1500

ALTERNATOR	50Hz
Brand and model	MECC ALTE ECP32-3L/4 (*)
Synchronous with electronic governor voltage	± 1%
Pole	4
Stator/rotator insulation	H
Protection level	IP23
Continuous power	75 kVA

(*) = or similar brand



Greenpower AB
 Helsingborgsvägen Varalöv
 262 96 Ängelholm
 Tel: 0431 - 222 40
 E-mail: info@greenpower.se
 web: www.greenpower.se